APPENDIX H

Transportation Impact Study

BUENA VISTA LAGOON ENHANCEMENT PROJECT

TRANSPORTATION IMPACT STUDY

Prepared for:

San Diego Association of Governments

Prepared by:



VRPA Technologies, Inc. 9520 Padgett Street, Suite 213 San Diego, CA 92126

In Association With:

AECOM

September 18, 2014

TABLE OF CONTENTS

CHAPTER	DESCRIPTION	PAGE
1	INTRODUCTION	1
1.1 1.2	Description of the Project Methodology	1 2
2	EXISTING CONDITIONS	5
2.1	Weir Basin	5
2.2	Railroad and Coast Highway Basins	5
2.3	I-5 Basin	5
2.4	Existing Traffic Conditions	5
3	IMPACTS	7
3.1	Trip Generation	7
3.2	Project Traffic	7
3.3	Bridge Construction Impacts	7
3.4	Traffic Impacts	7
3.5	Transit Impacts	7
3.6	Bicycle Impacts	8
3.7	Pedestrian Impacts	8

Appendix A – Project Trip Generation Information

LIST OF FIGURES

FIGURE DESCRIPTION

- 1-1 Project Vicinity1-2 Project Study Area
- 2-1 Existing Traffic Conditions
- 3-1 Project Trips Freshwater Alternative
- 3-2 Project Trips Saltwater Alternative
- 3-3 Project Trips Hybrid Alternative A
- 3-4 Project Trips Hybrid Alternative B

LIST OF TABLES

TABLE DESCRIPTION

2-1	Existing (2014) Street Segment Capacity Analysis
3-1	Project Trip Generation – Freshwater Alternative – Weir Basin
3-2	Project Trip Generation – Freshwater Alternative – Railroad and Coast Highway Basins
3-3	Project Trip Generation – Freshwater Alternative – I-5 Basin
3-4	Project Trip Generation – Saltwater Alternative – Weir Basin
3-5	Project Trip Generation – Saltwater Alternative – Railroad and Coast Highway Basins
3-6	Project Trip Generation – Saltwater Alternative – I-5 Basin
3-7	Project Trip Generation – Hybrid Alternative A – Weir Basin
3-8	Project Trip Generation – Hybrid Alternative A – Railroad and Coast Highway Basins
3-9	Project Trip Generation – Hybrid Alternative A – I-5 Basin
3-10	Project Trip Generation – Hybrid Alternative B – Weir Basin
3-11	Project Trip Generation – Hybrid Alternative B – Railroad and Coast Highway Basins
3-12	Project Trip Generation – Hybrid Alternative B – I-5 Basin

TRANSPORTATION IMPACT STUDY

Buena Vista Lagoon Enhancement Project

SAN DIEGO COUNTY, CALIFORNIA

This Transportation Impact Study (TIS) has been prepared for the purpose of analyzing transportation impacts expected due to the development of the Buena Vista Lagoon Enhancement Project (BVLEP) located in the Cities of Oceanside and Carlsbad in San Diego County.

1.1 DESCRIPTION OF THE PROJECT

The purpose of the proposed project is to enhance the biological and hydrological functions of the Buena Vista Lagoon to address increased sedimentation and invasive vegetation encroachment, as well as resulting declining coastal biodiversity, degrading water quality, water circulation restriction, and increased vector concerns. It is proposed to achieve these objectives through the following:

- ♦ Enhancement in all basins
- Vegetation removal to increase circulation/decrease vectors
- Infrastructure improvements where appropriate to increase circulation/prevent increases to flooding
- ♦ Improvements to public access by construction of recreational amenities, where possible, including a public boardwalk and fishing access
- Adaptive management strategies to maintain enhanced functions of the lagoon into the future

Four project alternatives are under consideration:

- ♦ Freshwater Alternative
- ♦ Saltwater Alternative
- Hybrid Alternative A
- Hybrid Alternative B

Figure 1-1 shows the project vicinity and Figure 1-2 shows the study area for transportation analysis.



1.2 METHODOLOGY


Project transportation impacts were analyzed according to regional guidelines for the San Diego region (<u>SANTEC/ITE Guidelines for the Preparation of Traffic Impact Studies in the San Diego Region</u>, March 2, 2000). The methodology can be summarized as follows:

- Determine the project trip generation (the number of daily and peak hour trips the project is expected to add to the roadway network)
- Determine whether a traffic impact analysis is necessary
- Determine the study area for detailed analysis of traffic impacts (if necessary)
- Analyze traffic impacts and recommend mitigation measures (if necessary)

Transit, bicycle, and pedestrian impacts of the project were also analyzed, but the methodology for this type of analysis is not specified in the guidelines and impacts were analyzed using accepted transportation engineering principles.







2.0 EXISTING CONDITIONS

The project is located in the Cities of Oceanside and Carlsbad in San Diego County. The analysis of traffic impacts was focused on three areas where construction staging areas are proposed to be located and access is proposed to be provided from the local roadway system. Existing conditions for each of these areas is described below.

2.1 WEIR BASIN

The Weir Basin is the westernmost of the four basins shown in Figure 1-2. Construction staging is proposed to occur at the south side of the basin. Access will be provided via Mountain View Drive, Ocean Street, Garfield Drive and Carlsbad Boulevard. In the vicinity of the project site, Mountain View Drive and Ocean Street are one-lane, one-way local streets, Garfield Drive is a two-lane, two-way arterial, and Carlsbad Boulevard is a divided arterial with one lane of traffic in each direction.

2.2 RAILROAD AND COAST HIGHWAY BASINS

The Railroad and Coast Highway Basins are the middle two of the four basins shown in Figure 1-2. Construction staging for both of these basins is proposed to occur along Carlsbad Boulevard/South Coast Highway north of the existing Carlsbad Boulevard Bridge. This roadway is named Carlsbad Boulevard in Carlsbad and South Coast Highway in Oceanside and the proposed staging area is near the boundary between the two cities. In the vicinity of the project site, Carlsbad Boulevard is a two-lane arterial street with bicycle lanes in each direction and a multi-use bicycle/pedestrian pathway provided west of the roadway. Farther to the north in Oceanside, South Coast Highway transitions into a four-lane, undivided arterial.

2.3 I-5 BASIN

The I-5 Basin is the easternmost of the four basins shown in Figure 1-2. Construction staging is proposed to occur at the south side of the basin along Jefferson Street in Carlsbad. Access will be provided via Jefferson Street toward SR 78 to the north and I-5 to the south and west. In the vicinity of the project site, Jefferson Street is a two-lane arterial with bicycle lanes in each direction of traffic.

2.4 EXISTING TRAFFIC CONDITIONS

Existing traffic conditions for 2014 are documented in Figure 2-1 and Table 2-1. The methodology for conducting this analysis can be described as follows:

- Existing daily traffic counts were obtained from the websites of Caltrans and SANDAG. Traffic counts were generally available only for years prior to 2014 and counts from previous years were updated to 2014 conditions using a growth factor of 2% per year. Traffic counts for some study area roadways were not available on the Caltrans and SANDAG websites and were estimated by VRPA Technologies.
- Capacity analysis was conducted using information contained in the SANTEC/ITE Guidelines mentioned in Chapter 1.



In traffic engineering methodology, roadway operations are rated in terms of level of service that range from level of service A (light traffic, minimal delays) to level of service F (traffic congestion, substantial delays). Level of service D is the typical standard for urban and suburban design. The results shown in Table 2-1 indicate that several study area roadways operate at level of service E or F indicating some level of traffic congestion, at least during the peak hours. These roadways include Interstate 5, State Route 78, Vista Way, South Coast Highway, and Carlsbad Boulevard. Other study area roadways were shown to be operating at level of service ranging from level of service A to level of service d, indicating that they would meet the typical design standards for traffic capacity.






Table 2-1 Existing (2014) Street Segment Capacity Analysis

				(2014 CC	STING ONDITIO	ONS)
ROADWAY	LOCATION	FUNCTIONAL CLASSIFICATION	DAILY CAPACITY AT LOS E	VOLUME	LOS	V/C
CARLSBAD VILLAGE DRIVE	Jefferson Street to I-5 SB Ramps	4-Lane Secondary Arterial/Collector	40,000	13,000	Α	0.33
	Jefferson Street to I-5 SB Ramps	4-Lane Secondary Arterial/Collector	40,000	21,400	С	0.54
	Jefferson Street to I-5 SB Ramps	4-Lane Major Arterial	40,000	31,300	D	0.78
INTERSTATE 5	SR 78 to Las Flores Dr	8-Lane Freeway	150,000	199,900	F	1.33
JEFFERSON STREET	Jefferson Street to I-5 SB Ramps	4-Lane Major Arterial	40,000	20,000	В	0.50
	Jefferson Street to I-5 SB Ramps	2-Lane Collector	15,000	9,300	С	0.62
LAGOON VIEW DRIVE	West of Jefferson Street	Local	2200 (1)	200 (2)	С	0.10
LAS FLORES DRIVE	Jefferson Street to I-5 SB Ramps	2-Lane Collector	15,000	9,400	С	0.63
MOUNTAIN VIEW DRIVE	Ocean Street to Carlsbad Blvd	Local	1100 (1)	300 (2)	С	0.27
SOUTH COAST HWY/ CARLSBAD BOULEVARD	Jefferson Street to I-5 SB Ramps	2-Lane Collector	15,000	25,000	F	1.67
	Jefferson Street to I-5 SB Ramps	2-Lane Collector	15,000	19,400	F	1.29
	Jefferson Street to I-5 SB Ramps	2-Lane Collector	15,000	13,200	E	0.88
	Jefferson Street to I-5 SB Ramps	4-Lane Secondary Arterial/Collector	30,000	16,700	С	0.56
STATE ROUTE 78	East of I-5	6-Lane Freeway	120,000	130,600	F	1.09
VISTA WAY	South Coast Hwy to I-5	2-Lane Collector	15,000	18,500	F	1.23

Note: Volume = Average Daily Traffic

LOS = Level of Service

V/C = Volume to Capacity Ratio

(1) Daily Capacity Estimated

(2) Existing Volume Estimated

3.0 IMPACTS

3.1 TRIP GENERATION

Project trip generation was calculated separately for each of the alternatives (Freshwater Alternative, Saltwater Alternative, Hybrid Alternative A, and Hybrid Alternative B) and each of the staging areas (Weir Basin, Railroad/Coast Highway Basins, and I-5 Basin). The result is twelve different trip generation calculations, as shown in Tables 3-1 through 3-12. The trip generation was based on project construction calculations, as shown in Appendix A.

3.2 PROJECT TRAFFIC

Figures 3-1 through 3-4 show project daily and peak hour traffic for each of the alternatives and staging areas.

3.3 BRIDGE CONSTRUCTION IMPACTS

For three of the four alternatives under consideration (Saltwater Alternative, Hybrid Alternative A, and Hybrid Alternative B), it will be necessary to narrow the roadway width of Carlsbad Boulevard in order to construct a new bridge over the waterway that connects the Railroad Basin and the Coast Highway Basin. During construction, it is proposed that the roadway that will be provided will include two fourteen-foot travel lanes, one lane in each direction for vehicle and bicycle traffic. Pedestrian travel will be prohibited and the existing multi-use pathway located on the west side of Carlsbad Boulevard will be closed. It is estimated that this closure related to construction will last for a period of nine months.

3.4 TRAFFIC IMPACTS

As described in Chapter 1, the SANTEC/ITE regional guidelines for traffic impact studies were used as the basis for determining traffic impacts. The guidelines specify that detailed traffic analysis be conducted for any roadway segments or intersections where a project will add 50 or more trips in the peak hour in either direction of travel. The guidelines are not specific regarding whether the threshold would change depending on whether the trips to be generated would be auto trips or truck trips. However, it is common transportation engineering practice whenever truck traffic is a substantial portion of project traffic to use passenger car equivalents (PCE's) to estimate the impacts of combined auto and truck traffic. For the purposes of this study, each truck was considered to be the equivalent of two passenger cars. Based on the calculations shown in Tables 3-1 through 3-12, there were no cases where the project would add 50 or more vehicles to the roadway network in either direction of traffic. Therefore, additional traffic analysis was not considered to be necessary.

3.5 TRANSIT IMPACTS

NCTD operates bus service along Carlsbad Boulevard/South Coast Highway through the study area via Route 101. Project construction is not expected to affect bus travel times or existing bus stops and the project is not considered to have any significant transit impacts.




3.6 BICYCLE IMPACTS


The construction of the Carlsbad Boulevard bridge will affect recreational and commuter bicyclists in different ways. For recreational bicyclists, the multi-use pathway will be closed temporarily during bridge construction and it is assumed that bicyclists who do not wish to share the roadway with vehicles will choose other locations for recreational travel. For commuter bicyclists, access will still be provided, but it will be less convenient because bicyclists will be sharing a fourteen-foot lane with vehicles rather than traveling in a separate lane as is possible with the existing roadway.


3.7 PEDESTRIAN IMPACTS

During construction of the Carlsbad Boulevard Bridge, pedestrians will be prohibited from using the roadway. Similar to the situation for recreational bicyclists, pedestrians who currently use the multipath trail to the west of the roadway for recreational purposes would be assumed to seek other locations for recreational walking. Given the relatively long distances involved, it is expected that very few pedestrians use the multi-purpose trail for employment, shopping, or other utilitarian purposes. For the few pedestrians who are in this category, there is no viable alternative route of travel and these pedestrians would need to change to other modes of travel (auto, transit, or bicycle) during bridge construction.












TABLE 3-1
Project Trip Generation
Freshwater Alternative - Weir Basin
Number of Trips

	TRI	TRUCKS			AUTOS			TOTAL PCE's		
PROJECT COMPONENT	Daily	Peak Hour		Daily	Peak Hour		Daily	Peak Hour		
	Dally	In	Out	Daily	ln	Out	Daily	In	Out	
Vegetation Removal	8	1	1	8	1	1	24	3	3	
Weir Replacement	8	1	1	8	1	1	24	3	3	
Total	16	2	2	16	2	2	48	6	6	

TABLE 3-2
Project Trip Generation
Freshwater Alternative - Railroad and Coast Highway Basin
Number of Trips

	TRUCKS			AUTOS			TOTAL PCE's		
PROJECT COMPONENT	Daily	Peak Hour		Daily	Peak	Hour	Daily	Peak Hour	
	Dally	In	Out	Daily	In	Out	Daily	In	Out
Vegetation Removal	84	5	5	10	1	1	178	11	11
Carlsbad Boulevard Bridge	16	1	1	15	2	4	47	4	6
Boardwalk	8	1	1	16	1	3	32	3	5
Total	108	7	7	41	4	8	257	18	22

TABLE 3-3
Project Trip Generation
Freshwater Alternative - I-5 Basin
Number of Trips

PROJECT COMPONENT	TRUCKS			AUTOS			TOTAL PCE's (1)		
	Daily	Peak Hour		Daily	Peak	Hour	Daily	Peak Hour	
		ln	Out	Daily	In	Out	Daily	ln	Out
Vegetation Removal	32	4	4	8	1	1	72	9	9
Total	32	4	4	8	1	1	72	9	9

TABLE 3-4
Project Trip Generation
Saltwater Alternative - Weir Basin
Number of Trips

	TRI	TRUCKS			AUTOS			TOTAL PCE's		
PROJECT COMPONENT	Daily	Peak Hour		Daily	Peak Hour		Daily	Peak Hour		
	Daily	In C	Out	Daily	In	Out	Daily	In	Out	
Vegetation Removal	8	1	1	8	1	1	24	3	3	
Weir Removal	8	1	1	8	1	1	24	3	3	
Total	16	2	2	16	2	2	48	6	6	

TABLE 3-5
Project Trip Generation
Saltwater Alternative - Railroad and Coast Highway Basin
Number of Trips

	TRUCKS			AL	AUTOS			TOTAL PCE's		
PROJECT COMPONENT	Daily	Peak Hour		Daily	Peak	Hour	Daily	Peak Hour		
	Daily	ln	Out	Daily	In	Out	Daily	ln	Out	
Vegetation Removal	84	5	5	10	1	1	178	11	11	
Carlsbad Boulevard Bridge	64	4	4	60	2	8	188	10	16	
Boardwalk	8	1	1	16	1	3	32	3	5	
Total	156	10	10	86	4	12	398	24	32	

TABLE 3-6
Project Trip Generation
Saltwater Alternative - I-5 Basin
Number of Trips

PROJECT COMPONENT	TRUCKS			AL	AUTOS			TOTAL PCE's (1)		
	Daily	Peak Hour		Daily	Peak Hour		Daily	Peak Hour		
	Dally	ln	Out	Daily	In	Out	Dally	In	Out	
Vegetation Removal	32	4	4	8	1	1	72	9	9	
Total	32	4	4	8	1	1	72	9	9	

TABLE 3-7
Project Trip Generation
Hybrid Alternative A - Weir Basin
Number of Trips

	TRI	TRUCKS			AUTOS			TOTAL PCE's		
PROJECT COMPONENT	Daily	Peak Hour		Daily	Peak Hour		Daily	Peak Hour		
	Daily	In C	Out	Daily	In	Out	Daily	In	Out	
Vegetation Removal	8	1	1	8	1	1	24	3	3	
Weir Removal	8	1	1	8	1	1	24	3	3	
Total	16	2	2	16	2	2	48	6	6	

TABLE 3-8
Project Trip Generation
Hybrid Alternative A - Railroad and Coast Highway Basin
Number of Trips

	TRUCKS			AU	AUTOS			TOTAL PCE's		
PROJECT COMPONENT	Daily	Peak Hour		Daily	Peak	Hour	Daily	Peak Hour		
	Dally	In	Out	Dally	In	Out	Dally	In	Out	
Vegetation Removal	84	5	5	10	1	1	178	11	11	
Carlsbad Boulevard Bridge	64	4	4	60	2	8	188	10	16	
Boardwalk	8	1	1	16	1	3	32	3	5	
Total	156	10	10	86	4	12	398	24	32	

TABLE 3-9
Project Trip Generation
Hybrid Alternative A - I-5 Basin
Number of Trips

	TRI	JCKS		AL	JTOS		TOTAL PCE's (1)						
PROJECT COMPONENT	Daily	Peak	Hour	Daily	Peak	Hour	Daily	Peak	Hour				
	Dally	ln	Out	Daily	In	Out	Daily	In	Out				
Vegetation Removal	32	4	4	8	1	1	72	9	9				
Total	32	4	4	8	1	1	72	9	9				

TABLE 3-10
Project Trip Generation
Hybrid Alternative B - Weir Basin
Number of Trips

	TRI	JCKS		AL	JTOS	-	TOTAL PCE's					
PROJECT COMPONENT	Daily	Peak	Hour	Daily	Peak	Hour	Daily	Peak	Hour			
	Dally	In	Out	Daily	In	Out	Daily	In	Out			
Vegetation Removal	8	1	1	8	1	1	24	3	3			
Weir Removal	8	1	1	8	1	1	24	3	3			
Total	16	2	2	16	2	2	48	6	6			

TABLE 3-11
Project Trip Generation
Hybrid Alternative B - Railroad and Coast Highway Basin
Number of Trips

	TRI	JCKS		AU	JTOS		TOTAL PCE's					
PROJECT COMPONENT	Daily	Peak	Hour	Daily	Peak	Hour	Daily	Peak	Hour			
	Dally	In	Out	Daily	In	Out	Dally	In	Out			
Vegetation Removal	84	5	5	10	1	1	178	11	11			
Carlsbad Boulevard Bridge	64	4	4	60	2	8	188	10	16			
Boardwalk	8	1	1	16	1	3	32	3	5			
Total	156	10	10	86	4	12	398	24	32			

TABLE 3-12
Project Trip Generation
Hybrid Alternative B - I-5 Basin
Number of Trips

	TRI	JCKS	_	AL	JTOS		TOTAL PCE's (1)					
PROJECT COMPONENT	Daily	Peak	Hour	Daily	Peak	Hour	Daily	Peak	Hour			
	Dally	ln	Out	Daily	ln	Out	Daily	In	Out			
Vegetation Removal	32	4	4	8	1	1	72	9	9			
Total	32	4	4	8	1	1	72	9	9			

APPENDIX A

PROJECT TRIP GENERATION INFORMATION

	9	-			4	-		- p																					
		Remarks			I funch are/bu		he raund tilp	Elicoti Oredge 17.			his every 10 days		hrs every 10 days		W cycle Kity										-				
		Total	4,137 4,137	111	3 2 2	\$ 5	2,037	313	ş	3 2	# 15	Ĕ ¢	÷	Ē	2 717.5	58					,	2 2 2 X	* *	===	<u> </u>			# 5	9 3
	Section Sectio	Number of Dera per	284 284 284 284 284 284 284 284 284 284	11	2 2 2	22	2.2	274 274 275	:	**	s E	22:	= %	75	351	žž						• • • •			2 ~ 2				
	Memaly	Dar par	97	99	222	22	22	293	2	22	3 8	9 9 8	3 2	97	aot aot	00 a			_		95	192 2	3 5	32:	2 2 2	222	2	9 9	9 9
	H Con No.	Trips					8								25										<u>-</u>				
	100000	Equipment Quantity p					- =		~			~	~	-	~ ^	~					-				:	N ~ -	-		
	S. MARRIED ST.	Productio				2. 2.		§ 	8	ą			98		8						ŝ	2		og .	1 g		ä		92
1	Thursday.	Grandly				34,500			23,621	Dyfee	8		653,000								<u>8</u>	2	·		9,000		3 34		
1 1 1 1 1 1 1 1 1 1		Remedi		nine/saresbane			of round by p	Coxt Dredge 1230			ryab 01/ma	Name of the same			oy cepacity	_				-			· ··						
		Total Equipment Hours	20 E 20 E	, s	* 2	1,938	26,04)	E 5	G.	3 2 3	81	5 5 8 8	101	å	2.59e 2.59e	3								225	g 5:	21.			
1		Number of Days par Elicipment																											
10 10 10 10 10 10 10 10	er Ahernative	Day per Equipment																											
10 10 10 10 10 10 10 10	san Was	Number of Tripe					M47,51								==		_				_								
1 1 1 1 1 1 1 1 1 1							- 2				- ,		~		~ ~ ~														
1 1 1 1 1 1 1 1 1 1					96		g,		8 8		6,800		985	8															_
Part	13-				8011				110,000																				
				resibesia									-	-	•	£	-							-	3.3				
1		┙	F P E S :	t hand		g R	~ .																						
10,145 1	10/4	Per Equi															2 2 1	X 21.0	# 17							••			
10 14 14 14 14 14 14 14	ra per Non	Present Equili																					• • • • • • • • • • • • • • • • • • • •						
10 14 14 14 14 14 14 14	Walar After	E 8											3 5				322	2 5 9	9 2	2									
10 14 15 15 15 15 15 15 15	I	i J											• • • • • • • • • • • • • • • • • • • •	=	a 					~									
10 14 15 15 15 15 15 15 15	H						- 4		-		-			~				~ ~ ~										TO-1	
10 Lidds	f J	1			87,		84.7	9	88,		893		,	2 ⁴			Z	2											
The state of the s	Zitte				900,654	171,000	362,000	49,000	69'69		000	88		000'68		1	 B	8											
Section 1995 The section of the sec	Power	Ē	33885	3 8 3	8	£ 8	£ 5	8 8	9 9 S	8 8 8	90,50	12	8 8		8 8 8		888	2 2 3	8 8	— <u>—</u>	8 8 8	5 5 5	8	83 8	888	<u></u>	888		8 % 8
[10] [1] 10 10 10 10 10 10 10	ŝ				5	ъ	G	b	5		Շ	ե					—												
क्षा दक्ष के अपने क्षा के के कि यह उन्हें के कि के का मान्य का प्रकार का प्रकार का प्रकार का प्रकार का प्रकार का	traction Method 1 - Fines to LA-5	Sest, Head Roads, Burjing Ares Maintenance	Final end to deter Messag grader Bushbos Dump Invok (3.3 CF) Wester Smoth.	T Bredge Luwon Area Bethow Frank-end baker Gemp boack (18.5 CF)	* Vegetation and Stockpile Amphibious harvester	ž	uving truck (14.5. Cr) 2 Sedinest with Oxedge Predig Lad's was parent Credig response vester	Rost - Stirvey craw for lagoon It Dradged Stad to Gorboride Besch wish Pipeline Broader assess	Und slung deach Duddoter	Front-survey trew for tysech	of Oreigned Sand (70-80%) to Naverhore with Pipeline Bosser pemp Boar	Bod -survey can for nearthque 1 Diedred Rim Grahad Sediment to Bute with Pipeline	evenint purp Genge (166) Crew boal (from/to Occessaide Herber)	I the Grahma Sediment by Berge to LA-5 ODMOS (30M tolids) Barge Tog	3NN BOM - NEVER CEN IN LAS	inigi Weir vater tile föuld weiterdam, pump, dig En wes Enne - install and remove collectom piles	Compression - three and termone collection pleas Pump Illysels (\$ to 1.3 it utes)	Free (16.5 CF) - Import material (street & concrete) Settlines (J. CF) - Parial well Combine cana	volkt selsky weir Blacktyse Trek - Vrnsport densolisked muserni to baedid	-5 Ways ber site (bild to flendam, pump, etc.) Create persons here a	Competed or when and tendore control any piece Competed or affect and tendore conference piece. Pump 1 to 1.5 it to be a	The first sector is the first teneral form of the first teneral form of the first feet form of the first feet feet form of the first feet feet feet feet feet feet feet fe	niet Chrenel Guide Ker ille Buld collection, pomp, etc] Ternier Ternier Listell fand fenner collection pier Dompitster effert and fennes on fender pier	Pung reparallen/escavation faction	Truck (18.5 of 7.+ Import armor material (noct) Beddiec (16.7) - pince material Beddiec (16.7) - pince material Designment and order (16.7) - pince material	elf Bain Chemes Golde (for Hybrid Alternative A Gny) er elte (butdroofferden, pann, etc.)	Crewist crans - install and remove confusions plass Compressor - cline and remove confusions place huma postback/ascession	Saching Chen vi guide Tout (3 of) - Vassion Compres	Trunc (40 ton) - place material

Construction Method 2 - Fines to Sycomore LandSil	_	1			fresh Wester	12/1		Company of the									i							
	E E	Archy Que	Quentity Oally Pro-	duction florante	The Rumbers	Perger Technical	i i	feet free free	- Garage	Guardet	Dank Pour	Princed Aum	humber of Reun	1	10.00				Feulement	A Pribrile A	A STATE OF		Same of the	1
The transport of the property	88 38 88 88 88 88 88 88 88 88 88 88 88 8	292Rr 907 00 02 9	00 THE TOTAL THE		est t	99999 929 22 25 393 2 2332 292 239 335 29	66552 and we we don't see	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	910	8 8 8 8		TOTAL	g 5 35 342 3 3538 358	# # # # # # # # # # # # # # # # # # #	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	i line salina 1 line	00 tal 10 000 tal 10 0	1.75 C C C C C C C C C C C C C C C C C C C	the table of the table of the table of the table of table	1 - 14	######################################	# # # # # # # # # # # # # # # # # # #	Ling SC(Lander) Ling SC(Lander) Signature (Lander) Signature (Land	44 33 P
		, e	ост	400	Ä				* \$8 § §	25 8 8 8 25	777 78 277 7	g a g		neg e pagg ****	22 × 123 × 225		8 8 8 8 8 8 1 1 1 1 1 1 1 1 1 1 1 1 1 1	8 8 8 8 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9				848 x 2 x 2 x 2 x 2 x 2 x 2 x 2 x 2 x 2 x		
D International department of the control of the co	82 22 29 3228	DON'T CONTROL OF THE	8 8 8 8	*** v * **	1369 M,035	222 222 2222	6 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	2 he read top 14 bal derer	5,500 1,600 1,000 1,000 1,000	8 8 8		84,1 250	9222 222 22 2222	8 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	25 25 25 25 25 25 25 25 25 25 25 25 25 2	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	000 000 000 000 000 000 000 000 000 00	27 0 8	77	2022 222 22 222	565 B # # B 85 85 85 85 85 85 85 85 85 85 85 85 85	1322 242 2c 193	2 hr need Eig 3.3 hr need Eig	

4	Τ											- 1													
Normal Section		arch area/hasin		dul purine	Ciften Dredge 1370	rry 10 den	ener/30 days			rs/1D days	reary/10 days	equipment legis	hound/10 days	eduliment locks											
Total	31333	***	8 8				ž _	8	£ 25			761		•	s							# 51 B			
passes of	85333								. 111					_											# 2 # 1
in the same	23333	223	32	22					2 22:							**********			22 22			~ 52			
Manager of														_		·				-	~	2 22		223	2 335
allowers and the second								~	~																2
Dally Preduction			95			8	3	8	8	â		8		4,68		··						- 3*	~~		
Quantity					80		997117						_						A		£	3.5		<u>s</u>	<u>.</u>
1	-	1	<u> </u>		ž.	ž .	====	136.50		00/3/2	007.03	altra Satra		nclo 261,000				I .			\$	33	Ê		8 3
Brade		Sycare danual L		1 hround trip		e Novembrie	Spend to day			a hours/10 days	* houn/30 days	other aquipment	A two-syllo days	ather aquipment i											
Total Davigment Hours	22222	***	* 5	25,041	§ 8	3 55	s !	9 9	25.25	e 63	3	E 1	. H 5	£						,	# 4 5	= 35	I 2		
Number of Dept per festionent	88888	222	58	8.5	9.5	2 2 2	٤ ;	2 5	: 835	ā ¤s	: 2	2 1	2 2 3									~ 35	n :		
Hours per Day per Carloment	33333	223	92	22	255	2 2 2	3 3	2 2	333	3 33	3	2 2	93	2						:	111	2 32	2 2		
Number of Tripe				12,78			···															ŧ			
Seakonent Quentity per Day			H N	- 2							-			-								- 3~,			
De fly Preduction			3£.		8	8	8,	600	3	8	8	3		8							3	8 8			-
Querreloy			on the		8,1	414,000	2000	00784	DEC'ALS	0007242	187,000	457,000		357,000							}	88			
Enech		ran/Jards	•	2	oru si		£			Ę.			E	ent Include									_		
		- Sunti		7 Proces	Ellicen Bridge 1370		Official of				a boury 10 day		# houn,'so days	ather squips											
Total France	55555	2 8 8	8 5	21.00 E	ğţa	ğ 9:	3	. 1	3 4 2	2 % F	× ;	g g	100 100	ž	3 %	2 03	2 2-								
Days per Days per	99999	8 2 2	2.2	* *	999	<u> </u>	E 8	я	282		2 1	x	* 2	9											
Mandey of Models per Trips Courpment	39999	222	33	11	22.2	299	2 2	2	292	2 2 3	3 5	3	93	9	32	3 33	9 22								
Tries				an,	<u> </u>				•••							~	~								
Quentity par ber			- "	- 12			۰ ~	*						-		~ ~ ~									
My Production			867		8	8	3	8	ĝ	ş	ĝ	ĝ		ş	š	2									
Quantity Delty		 -	00	Harry Cit	8	orra	416,000	oorbs	00000	80,79	00071	ood (ca)		971	 §	8									
Pover the (HP)	8 B B S E	885	B #	8 2	3 8 8	2 2 2		8	8888					~ 8	2 2 2		2.5	9 9 9	50 00	8:	89	8 5 8 8		888 0	R S D
3		-	ð i	ă	6	ъ	6	-	δ	6	6			t		5		5				4 229 45	5	5 8 8 8 5 8 8 8	24 %
											Ter Children	- Injustra		ž											
Constitution Milling 3 - Fines to Overdredged Mt	A life finesh, citating for a Malatenance front and bade front bade for a fine fine for a fine fine for a fine fine fine fine fine for a fine fine fine fine fine fine fine fine	Batchee Front-and baseler Derive Dock [16.5 Cr]	Section to a source of a section of a sectio	Immigrat vigigations is becomen tradifie. 72 infes regard jety. Damp track (16.5 Cr). Referent tets forester	Design Cal. Graph 1347 with pure Overlie 1347 with pure Overlie 1347 with pure Overlie 1444 within	Gestruc Oweringted Ph Dreight (LB) with perso Dreight Support result Bost - Savey Dea the lapose	eszembed szack so Dzeamskie Beach with publifier Noories gump	asternard send to Horth Cashbad Reach with pipulos boosterpung	princia had delegations sendostri Remover all backer Francia selections are delegations. The delegation in the graph delegations are delegations.	of Drafest Stand (70-m2N) to Nearrhore with Platfine Booster pump Post Boost servity orac for manibose	ercented fine grained soll from DI Bacin to workpite in 1-5 Basin Boat	Nockelt fire serined self-them roadsplie to Counteethed bit wilds Oredge (187) with perms Oredge rapport wassel	both - terrey trew for lapson	Box.	ADVICE MAY WITH COMPANY THE COMPANY THE COMPANY OF COMPANY COM	Institution week (1 to 1.5 m biology) Viryal 15.5 Gy) - Steport maleutal (strail & concrete) Healthook (2 Gy) - Aulid week Comifer prine	bb volating wat Blackos Track - brongest demottished mararial to baselts	S-5 You'r Franker Come - Instit their notive query, wit; Cranker Come - Instit their technologies of Cranker place Crankerson - effet and remove cofferdem place Purpy	Write vert for e. I. il in ital. Tract (14.5 cm - wapon material (steal & caccus) Battoe (1.04) - kuld wait Creder one	hake Comme dudge water the [half cellertath, comp. etc] Cardet cannot from land water principles Cardethalo, etchy and emorar cellertam also	Verigi pretiden/accession action	lives) charves guide Treat, list. Cro. Vegot erroer mare fal (mod.) Francisco (L. Cro.) plara morandal Francisco (L. Cro.), place material Crossisco mare	if Brain Charnel Colde (for Hybrid Alemathia A Orby) It the Quotis collection, palog, etc.)	Constitution and and inness calculus piles Constitution of deep and inness coleration plass Famp Totale deep cannot done	Sakel gride vot (10 v. benkelst bennet vot (10 v. benkelst series) vot end lineder (5 CT) - place material
Const	4				Σ		Trampert	Traspart	i jenet i	Transport	Transport	Томрет			a a	Í	ž.	Controlled	!	Construct takes Demarker Co	å	Ž.	Compress W Deman	3	

.